



100 Ton Ironworker 230V, 3Ph, PowerLink, Coper Notcher & 2 LED Lights

Product Images





Short Description

100 Ton Ironworker 230V, 3Ph, PowerLink, Coper Notcher & 2 LED Lights

Additional Information

| Stock Number | ED9-10233512 |
|--|------------------------------|
| Amps | 22 |
| Flat Bar Shear Max Capacity 1" | 10 |
| Flat Bar Shear Max Capacity 3/4" | 14 |
| Flat Bar Shear Max Capacity (In.) | 3/4 x 14, 1 x 10 |
| Flat Bar Shear Max Round Capacity (In.) | 1-1/4 |
| Flat Bar Shear Max Round (In) | 1-1/4 |
| Flat Bar Shear Max Square Capacity (In.) | 1-1/4 |
| Flat Bar Shear Max Square (In) | 1-1/4 |
| Flat Bar Shear Work Height (In.) | 37 |
| Hydraulic Pump (GPM) | 10-1/2 |
| Hydraulic Reservoir (Gal.) | 17 |
| Hydraulics (GPM) | 10-1/2 |
| Hydraulics (PSI) | 3500 |
| Model Number | 10233512 |
| Motor Amps | 22 |
| Motor (HP) | 7.5 HP 3 ~ 230V |
| Motor Speed (RPM) | 1765 |
| Open Station Throat Depth (In) | 14-3/4 |
| Open Workstation Throat Depth (In.) | 14-3/4 |
| Open Workstation Work Height (In.) | 37 |
| Product Dimensions (In.) | 56-1/8 x 45 x 61-11/16 |
| Prop 65 | Cancer and Reproductive Harm |
| Punch Max Capacity (In.) | 1-1/16 dia in 1" A36" |
| Punch Open Height (In) | 8-3/4 |
| | |

| Punch Rating (Tons) | 100 |
|---------------------------------------|--------------|
| Punch Shut Height (In) | 6-15/16 |
| Punch Stroke (In.) | 1-13/16 |
| Punch Throat Depth (In.) | 11 |
| Punch Work Height (In.) | 39-1/16 |
| Rating (Tons) | 100 |
| Shipping Dimensions (L x W x H) (In.) | 46 x 69 x 67 |
| Valve Pressure (PSI) | 3500 |
| Warranty | 1 Year |
| Gross Weight | 4650.0 |
| Net weight | 4557.0 |

