



100 Ton Ironworker 575V, 3Ph

Product Images



Short Description

100 Ton Ironworker 575V, 3Ph

Additional Information

Stock Number	ED9-IW100-3P575
Amps	8
Angle Shear Max Capacity 1/2"	6 x 6
Angle Shear Max Capacity (In.)	6 x 6 x 1/2
Angle Shear Work Height (In.)	43-15/16
Coper Notcher Max Capacity (In.)	2-1/2 x 6 x 1/2
Coper Notcher Work Height (In.)	42
Flat Bar Shear Max Capacity 1"	10
Flat Bar Shear Max Capacity 3/4"	14
Flat Bar Shear Max Capacity (In.)	3/4 x 14, 1 x 10
Flat Bar Shear Max Round Capacity (In.)	1-1/4
Flat Bar Shear Max Round (In)	1-1/4
Flat Bar Shear Max Square (In)	1-1/4
Flat Bar Shear Rating (Tons)	100
Flat Bar Shear Work Height (In.)	37
Gross Weight (Lbs)	4650
Hydraulic Pump (GPM)	10-1/2
Hydraulic Reservoir (Gal.)	17
Hydraulics (GPM)	10-1/2
Hydraulics (PSI)	3500
Model Number	IW100-3P575
Motor Amps	8
Motor (HP)	7.5 HP 3 ~ 575V
Motor Speed (RPM)	1765
Open Workstation Throat Depth (In.)	14-3/4

Open Workstation Work Height (In.)	37
Overall Dimensions (L x W x H) (In.)	45 x 56-1/8 x 61-11/16
Product Dimensions (In.)	56-1/8 x 45 x 61-11/16
Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	1-1/16 diam. in 1 mild steel
Punch Open Height (In)	8-3/4
Punch Rating (Tons)	100
Punch Shut Height (In)	6-15/16
Punch Stroke (In.)	1-13/16
Punch Work Height (In.)	39-1/16
Rating (Tons)	100
Reservoir (Gal.)	17
Shipping Dimensions (L x W x H) (In.)	46 x 69 x 67
Valve Pressure (PSI)	3500
Warranty	1 Year
Weight (Lbs.)	4650
Gross Weight	4650.0
Net weight	4557.0



