



120 Ton Ironworker 460V, 3Ph, with PowerLink

Product Images



Short Description

120 Ton Ironworker 460V, 3Ph, with PowerLink

Additional Information

Stock Number	ED9-IW120-3P460-A
Amps	12
Angle Shear Max Capacity 1/2"	6 x 6
Angle Shear Work Height (In.)	52-1/2
Coper Notcher Max Capacity (In.)	3 x 6 x 1/2
Coper Notcher Work Height (In.)	40
Flat Bar Shear Max Capacity 1"	12
Flat Bar Shear Max Capacity 1/2"	24
Flat Bar Shear Max Capacity (In.)	24
Flat Bar Shear Max Round Capacity (In.)	1-1/4
Flat Bar Shear Max Round (In)	1-1/4
Flat Bar Shear Max Square (In)	1-1/4
Flat Bar Shear Rating (Tons)	120
Flat Bar Shear Work Height (In.)	33-1/4
Gross Weight (Lbs)	5856
Hydraulic Pump (GPM)	24
Hydraulic Reservoir (Gal.)	17
Hydraulics (GPM)	24
Hydraulics (PSI)	3800
Model Number	IW120-3P460-AC900
Motor Amps	12
Motor (HP)	10 HP 3 ~ 460V
Motor Speed (RPM)	1770
Overall Dimensions (L x W x H) (In.)	60 x 60 x 84
Overall Height (In.)	87

Product Dimensions (In.)	60 x 60 x 84
Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	120 Tons
Punch Open Height (In)	9-1/8
Punch Rating (Tons)	120
Punch Shut Height (In)	7-1/8
Punch Stroke (In.)	2
Punch Work Height (In.)	9.125
Rating (Tons)	120
Reservoir (Gal.)	17
Shipping Dimensions (L x W x H) (In.)	60 x 67 x 87
Valve Pressure (PSI)	3800
Warranty	1 Year
Weight (Lbs.)	5500
Gross Weight	5975.0

