



# 50 Ton Ironworker 230V, 3Ph with PowerLink

## Product Images

---



## Short Description

---

50 Ton Ironworker 230V, 3Ph with PowerLink

Stock Number	ED9-IW50-3P230-A
Amps	7
Angle Shear Max Capacity 1/4"	4 x 4
Angle Shear Work Height (In.)	39-7/8
Coper Notcher Max Capacity (In.)	2 x 3 x 5/16
Coper Notcher Work Height (In.)	39-1/2
Flat Bar Shear Max Capacity 1/2"	10
Flat Bar Shear Max Capacity 3/4"	4
Flat Bar Shear Max Capacity (In.)	1/2" x 10", 3/4" x 4"
Flat Bar Shear Max Round (In)	3/4
Flat Bar Shear Max Square (In)	3/4
Flat Bar Shear Rating (Tons)	50
Flat Bar Shear Work Height (In.)	34-1/2
Gross Weight (Lbs)	2020
Hydraulic Pump (GPM)	3-1/2
Hydraulics (GPM)	3-1/2
Hydraulics (PSI)	2500
Model Number	IW50-3P230-AC500
Motor Amps	14
Motor (HP)	5 HP 3 ~ 230V
Motor Speed (RPM)	1725
Overall Dimensions (L x W x H) (In.)	36-3/4 x 36-1/8 x 54-1/2
Product Dimensions (In.)	36-3/4 x 36-1/8 x 54-1/2
Prop 65	Cancer and Reproductive Harm
<b>Additional Information</b>	
Punch Max Capacity (In.)	1 diam. in 5/8 mild steel
Punch Open Height (In)	8-1/8

Punch Rating (Tons)	50
Punch Shut Height (In)	6-1/4
Punch Stroke (In.)	1-7/8
Punch Throat Depth (In.)	7
Punch Work Height (In.)	36-9/16
Rating (Tons)	50
Reservoir (Gal.)	7
Shipping Dimensions (L x W x H) (In.)	45 x 51 x 62
Valve Pressure (PSI)	2750
Warranty	1 Year
Weight (Lbs.)	2020
Gross Weight	2020.0

