



50 Ton Ironworker 460V, 3Ph with PowerLink

Product Images



Short Description

50 Ton Ironworker 460V, 3Ph with PowerLink

| | |
|---|------------------------------|
| Stock Number | ED9-IW50-3P460-A |
| Amps | 7 |
| Angle Shear Max Capacity 1/4" | 4 x 4 |
| Angle Shear Work Height (In.) | 39-7/8 |
| Coper Notcher Max Capacity (In.) | 2 x 3 x 5/16 |
| Coper Notcher Work Height (In.) | 39-1/2 |
| Flat Bar Shear Max Capacity 1/2" | 10 |
| Flat Bar Shear Max Capacity 3/4" | 4 |
| Flat Bar Shear Max Capacity (In.) | 1/2" x 10", 3/4" x 4" |
| Flat Bar Shear Max Round (In) | 3/4 |
| Flat Bar Shear Max Square (In) | 3/4 |
| Flat Bar Shear Rating (Tons) | 50 |
| Flat Bar Shear Work Height (In.) | 34-1/2 |
| Hydraulic Pump (GPM) | 3-1/2 |
| Hydraulics (GPM) | 3-1/2 |
| Hydraulics (PSI) | 2500 |
| Model Number | IW50-3P460-AC500 |
| Motor Amps | 7 |
| Motor (HP) | 5 HP 3 ~ 460V |
| Motor Speed (RPM) | 1725 |
| Overall Dimensions (L x W x H) (In.) | 36-3/4 x 36-1/8 x 54-1/2 |
| Product Dimensions (In.) | 36-3/4 x 36-1/8 x 54-1/2 |
| Prop 65 | Cancer and Reproductive Harm |
| Punch Max Capacity (In.) | 1 diam. in 5/8 mild steel |
| Additional Information Punch Open Height (In) | 8-1/8 |
| Punch Rating (Tons) | 50 |

| | |
|---------------------------------------|--------------|
| Punch Shut Height (In) | 6-1/4 |
| Punch Stroke (In.) | 1-7/8 |
| Punch Throat Depth (In.) | 7 |
| Punch Work Height (In.) | 36-9/16 |
| Rating (Tons) | 50 |
| Reservoir (Gal.) | 7 |
| Shipping Dimensions (L x W x H) (In.) | 45 x 51 x 62 |
| Valve Pressure (PSI) | 2750 |
| Warranty | 1 Year |
| Gross Weight | 2020.0 |
| Net weight | 1980.0 |

