



65 Ton Ironworker 575V, 3Ph, with PowerLink

Product Images



Additional Information

| | |
|---|--------------------------------|
| Stock Number | ED9-IW65-3P575-A |
| Amps | 8 |
| Angle Shear Max Capacity 3/8" | 5 x 5 |
| Coper Notcher Max Capacity (In.) | 2-1/2 x 5 x 3/8 |
| Coper Notcher Work Height (In.) | 39-1/2 |
| Flat Bar Shear Max Capacity 1/2" | 14 |
| Flat Bar Shear Max Capacity 3/8" | 24 |
| Flat Bar Shear Max Capacity (In.) | 3/8 x 24, 1/2 x 14, 1x4 |
| Flat Bar Shear Max Round Capacity (In.) | 1 |
| Flat Bar Shear Max Round (In) | 1 |
| Flat Bar Shear Max Square (In) | 1 |
| Flat Bar Shear Rating (Tons) | 65 |
| Flat Bar Shear Work Height (In.) | 34-1/2 |
| Gross Weight (Lbs) | 4750 |
| Hydraulic Pump (GPM) | 10-1/2 |
| Hydraulic Reservoir (Gal.) | 17 |
| Hydraulics (GPM) | 10-1/2 |
| Hydraulics (PSI) | 3500 |
| Model Number | IW65-3P575-AC600 |
| Motor Amps | 8 |
| Motor (HP) | 7.5 HP 3 ~ 575V |
| Motor Speed (RPM) | 1770 |
| Overall Dimensions (L x W x H) (In.) | 45 x 62-1/8 x 57 |
| Prop 65 | Cancer and Reproductive Harm |
| Punch Max Capacity (In.) | 1-1/16 diam. in 3/4 mild steel |

| | |
|---------------------------------------|--------------|
| Punch Open Height (In) | 8-3/4 |
| Punch Rating (Tons) | 65 |
| Punch Shut Height (In) | 6-15/16 |
| Punch Stroke (In.) | 1-13/16 |
| Punch Work Height (In.) | 36-9/16 |
| Rating (Tons) | 65 |
| Reservoir (Gal.) | 17 |
| Shipping Dimensions (L x W x H) (In.) | 46 x 69 x 63 |
| Valve Pressure (PSI) | 3500 |
| Warranty | 1 Year |
| Weight (Lbs.) | 4750 |
| Gross Weight | 4750.0 |

