



65 Ton Ironworker 230V, 3Ph

Product Images



Short Description

65 Ton Ironworker 230V, 3Ph

Additional Information

Stock Number	ED9-IW65-3P230
Amps	22
Angle Shear Max Capacity (In.)	5 x 5 x 3/8
Angle Shear Work Height (In.)	43-1/2
Coper Notcher Max Capacity (In.)	2-1/2 x 5 x 3/8
Coper Notcher Work Height (In.)	39-1/2
Flat Bar Shear Max Capacity 1/2"	14
Flat Bar Shear Max Capacity 3/8"	24
Flat Bar Shear Max Capacity (In.)	3/8 x 24, 1/2 x 14, 1x4
Flat Bar Shear Max Round Capacity (In.)	1
Flat Bar Shear Max Round (In)	1
Flat Bar Shear Max Square (In)	1
Flat Bar Shear Rating (Tons)	65
Flat Bar Shear Work Height (In.)	34-1/2
Gross Weight (Lbs)	4750
Hydraulic Pump (GPM)	10-1/2
Hydraulic Reservoir (Gal.)	17
Hydraulics (GPM)	10-1/2
Hydraulics (PSI)	3500
Model Number	IW65-3P230
Motor Amps	22
Motor (HP)	7.5 HP 3 ~ 230V
Motor Speed (RPM)	1765
Overall Dimensions (L x W x H) (In.)	45 x 62-1/8 x 57
Prop 65	Cancer and Reproductive Harm

Punch Max Capacity (In.)	1-1/16 diam. in 3/4 mild steel
Punch Open Height (In)	8-3/4
Punch Rating (Tons)	65
Punch Shut Height (In)	6-15/16
Punch Stroke (In.)	1-13/16
Punch Work Height (In.)	36-9/16
Rating (Tons)	65
Reservoir (Gal.)	17
Shipping Dimensions (L x W x H) (In.)	46 x 69 x 63
Valve Pressure (PSI)	3500
Warranty	1 Year
Weight (Lbs.)	4750
Gross Weight	4750.0

