



75 Ton Ironworker 208V, 3Ph, with PowerLink

Product Images



Short Description

75 Ton Ironworker 208V, 3Ph, with PowerLink

Additional Information

Stock Number	ED9-IW75-3P208-A
Amps	22
Angle Shear Max Capacity (In.)	5 x 5 x 1/2
Angle Shear Work Height (In.)	43-15/16
Coper Notcher Max Capacity (In.)	2-1/2 x 5 x 1/2
Coper Notcher Work Height (In.)	42
Flat Bar Shear Max Capacity 1/2"	14
Flat Bar Shear Max Capacity 3/4"	10
Flat Bar Shear Max Capacity (In.)	1/2 x 14, 3/4 x 10
Flat Bar Shear Max Round Capacity (In.)	1
Flat Bar Shear Max Round (In)	1
Flat Bar Shear Max Square (In)	1
Flat Bar Shear Rating (Tons)	75
Flat Bar Shear Work Height (In.)	37
Gross Weight (Lbs)	4100
Hydraulic Pump (GPM)	10-1/2
Hydraulic Reservoir (Gal.)	17
Hydraulics (GPM)	10-1/2
Hydraulics (PSI)	3500
Model Number	IW75-3P208-AC600
Motor Amps	22
Motor (HP)	7.5 HP 3 ~ 208V
Motor Speed (RPM)	1765
Overall Dimensions (L x W x H) (In.)	45 x 50 x 60-1/4
Product Dimensions (In.)	50 x 45 x 60-1/4

Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	1-1/6 diam. in 7/8 mild steel
Punch Open Height (In)	8-3/4
Punch Rating (Tons)	75
Punch Shut Height (In)	6-15/16
Punch Stroke (In.)	1-13/16
Punch Work Height (In.)	36-9/16
Rating (Tons)	75
Reservoir (Gal.)	17
Shipping Dimensions (L x W x H) (In.)	46 x 69 x 63
Valve Pressure (PSI)	3500
Warranty	1 Year
Weight (Lbs.)	4100
Gross Weight	4100.0

